

10K

SOLARATOR SERIES

Operates Seamlessly with Generator: Experience Uninterrupted Power, Even in Areas with Grid Instability

S6-EH1P10K03-NV-YD-L-AU

Single Phase | Low Voltage



- Supports up to 20A PV input current, compatible with future higher-power PV modules
- 200% overload for 10s in off-grid mode, ensuring stable startup of motors, water pumps and air conditioners
- Seamless on/off-grid switching in under 10ms, guaranteeing an uninterrupted power supply
- More battery options, compatible with any battery (between 40V-60V)
- Supports existing PV grid-tied power connection for export control and off-grid use
- Multiple methods of generator connection and auto control, enabling flexible local deployment
- Support max 6 units in parallel, expanding system capacity
- Smart Load management, extending backup time for critical loads
- Customizable battery backup level for uninterrupted power
- Supports PV-only off-grid operation, reducing upfront costs
- AI-Powered & VPP-Ready - maximise savings, unlock additional income
- 7-inch industrial-grade LCD screen, providing a larger, user-friendly interface for local operation
- Ingress protection IP66, for operation in harsh conditions

AUSTRALIA

t: +61 1800928995 e: sales@solisinverters.com.au w: solisinverters.au
+61 3 8555 9516 service@solisinverters.com.au



DATASHEET

Models	10K
Input DC (PV side)	
Recommended max. PV array size	20 kW
Max. input voltage	550 V
Rated voltage	380 V
Start-up voltage	100 V
MPPT voltage range	100 - 450 V
Max. input current per MPPT	40 A / 40 A / 40 A
Max. current per DC input	20 A
Max. short circuit current	50 A / 50 A / 50 A
MPPT number / Max. input strings number	3 / 6
Battery	
Battery type	Li-ion / Lead-acid
Battery voltage range	40 - 60 V
Max. charge / discharge current	207 A
Number of battery port / Number of BMS Port	1 / 1
Communication	CAN / RS485
Output AC (Grid side)	
Rated output power	9.999 kW
Max. / Rated apparent output power	9.999 kVA
Rated grid voltage	L/N/PE, 230 V
Rated grid frequency	50 Hz
Rated grid output current	43.5 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
THDi	< 3%
Input AC (Grid side)	
Max. input power	14.49 kW
Input voltage range	187 - 253 V
Max. input current	63 A
Frequency range	45 - 55 Hz
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
Output AC (Back-up)	
Rated output power	9.999 kW
Rated apparent output power	9.999 kVA
Max. apparent output power	2 times of rated power, 10 s
Back-up switch time ^①	< 10 ms
Rated output voltage	L/N/PE, 230 V
Rated frequency	50 Hz
Rated output current	43.5 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
THDv (@linear load)	< 3%
Input AC (Generator side)	
Max. input power	9.999 kW
Max. input current	43.5 A
Rated input voltage	L/N/PE, 230 V
Rated input frequency	50 Hz
Power factor	> 0.99 (0.8 leading - 0.8 lagging)
Efficiency	
Max. efficiency	97.60%
EU efficiency	97.00%
BAT charged by PV/AC max. efficiency	> 94.90% / > 94.33%
Battery discharged efficiency	93.51%
Protection	
Surge protection	Yes
Output over current protection	Yes
Insulation resistance monitoring	Yes
Residual current detection	Yes
Integrated PV switch	Yes
DC reverse-polarity protection	Yes (PV only)
Protection class / Over voltage category	I / II (PV and BAT), III (MAINS and BACKUP and GEN)
Active anti-islanding method	Frequency Shift
General Data	
Dimensions (W × H × D)	459 × 845 × 313 mm
Weight	55.5 kg
Inverter topology	Non-isolated (PV), Isolated (Battery)
Self-consumption	< 40 W
Operating temperature range	-25 ~ +60°C
Relative humidity	0 - 100%
Ingress protection	IP66
Noise emission (typical)	< 65 dB(A)
Cooling concept	Intelligent redundant fan-cooling
Max. operation altitude	4000 m
Grid connection standard	AS 4777
Safety / EMC standard	IEC/EN 62109-1/-2, EN 61000-6-2/-3
Features	
PV connection	MC4 connector
Battery connection	Terminal Block
AC connection	Terminal Block
Display	7.0" LCD display & Bluetooth + APP
Communication interface	Standard: WIFI+Bluetooth, CAN-BMS, CAN-Parallel×2, RS485-Meter, RS485, DRM, DI, DO×2; Optional: 4G, LAN

① From On-Grid Mode to Off-Grid Mode: For a single inverter system, switchover time <10ms. For a parallel system which consists of up to 6 inverters, switchover time <20ms. If customer wishes to connect more than 6 inverters in parallel, please contact Solis Technical Team.